

GLASS & MIRRORS

MAGIC MIRROR V2

The MAGIC MIRROR allows the image area of the ad notam monitor system to appear in the "ON" position and completely vanish when turned "OFF" leaving a 100% homogeneous mirror surface on the front.

The MAGIC MIRROR is is designed for combination with the ad notam monitor systems and fullfills the necessary surface, hardness, and tension qualities.

The position of the image area within the mirror surface is freely selectable. The flexibility is only limited by the outline dimensions of the ad notam monitor system which need to be considered when installing the monitor system on the backside of the mirror.

Please use the ad notam glass orderform as appendix to your purchase order to supply data.

Transmission of image area: 40% +/-5Reflection of mirror surrounding image area: 60% +/-5Reflection of image area: 60% +/-5



ARTICLE NO.

Art.No.		Code	Thickness	Туре
MM-SM V2	-	-005 R	5mm	Standard Float
		-009 R	8.8mm	Laminated Safety Glass (LSG)



GLASS & MIRRORS

MAGIC MIRROR V2

TECHNICAL SPECIFICATION

Characteristics	MM-SM-V2-005 R	MM-SM-V2-009 R
Tint	silver	silver
Thickness	5mm	8.8mm
Weight per square meter	12.5kg	22kg
Max. dimensions	3150 x 2000mm	3150 x 2000mm
Combinable monitor system sizes	13.3" - 84.0"	13.3" - 84.0"

Tolerances	Application Characteristics	Cleaning Note
If the difference between ordered dimensions and actual received product exceeds 2mm (ca. 1/16") in measurement of the height and width, the material is defective. In this case the glass may be exchanged at no charge. Slightly optical irritations on the surface of the material may appear as accumulations of very small black spots. This is due to the characteristics of the material and it is not possible to avoid or clean this effect. Please check immediately after receiving your goods if one of these accumulations exceeds an area of 3 square centimeter	ad notam glass and mirror types are suitable in moist areas but for indoor use only! Standard products are not usable in public facilities or in public places. Please consider this with your order or planning. The specified mirror is suitable in moist areas but it must not be exposed to a continous flow of water as for example in showers Due to the material properties, the mirror also must not be exposed to direct sunlight. Installation and mounting guidelines for glass have to be considered! Upon request authorized retailers can be supported with	Do not use any rubbing cleaning materials! Use only a clean and dust-free cloth, by using standard glass detergents! Check the material specification!
(ca. 1 3/16 square inches).	training!	
Facetted areas may appear with a slightly deviating shade.	Please note that due to the material properties, the brightness of the monitor system and the reflectivity of the mirror are somewhat affected.	